



Submittal Data Sheet

Series Name: BLU+ Multi Zone Regular HeatSeries

Heat Pump System	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



Item	Unit	Specification
Performance Data		
Cooling Capacity* Heating Capacity*	Btu/h	23,400
Design Pressure Refrigerant Type	Btu/h	25,000
Liquid Side Gas Side Drain Pipe	PSIG	550 / 340
Size Indoor Operation Range of	-	R454b
Cooling Indoor Operation Range of	inch(mm)	3/8" (9.52mm)
Heating	inch(mm)	5/8" (15.9mm)
	inch(mm)	1" (25m m)
	Deg.°F (°C)	60°F~90°F (16°C~32°C)
	Deg.°F (°C)	32°F~86°F (0°C~30°C)
Electrical		
Normal Operational Voltage	V, Ph, Hz	208/230V,1Ph, 60Hz
Voltage Range	V	187-253
Connection Wiring	-	AWG 14/4
MCA	A	3.0
Indoor Fan Motor Model	-	ZKFN-45-8-1
Indoor Fan Motor Output	W	45
Indoor Fan Motor RLA	A	1
Indoor Fan Motor Speed(Hi/Mi/Lo)	r/m in	624 / 568 / 426
Air Flow & Noise Level		
Indoor Air Flow (H/M/L)	CFM	765 / 706 / 636 / 547 / 547
Indoor Noise Level (H/M/L)	dB(A)	49 / 45 / 43 / 34 / 34
Dimension (W×D×H)	inch	32-5/8 x 32-5/8 x 8-1/8
	mm	830 × 830 × 205
Package (W×D×H)	inch	35-7/8 x 35-7/8 x 9-7/8
	mm	910 × 910 × 250
Net Weight / Gross Weight	lbs	47 / 59
	kg	21.4 / 26.8

*Standard capacity of indoor unit is for reference, capacity varies based on Multi-zonesystem combinations.

NG products are subject to continuous improvements. NG reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations.

Actual unit design may differ from images shown in this submittal sheet.

Indoor Unit Dimension

