



# Submittal Data Sheet

Series Name:NG BLU+ SINGLE ZONE SERIES

High Wall Heat Pump System	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION	
Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	347.3 / 294.3 / 194.2 / 153.0 / 153.0
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	46/41/35/24/18.5
Dimension (WxDxH)	inch 31.57 x 7.87 x 11.61
	mm 802.0x200.0x295.0
Package (WxDxH)	inch 34.45 x 11.22 x 14.96
	mm 875x285x380
Net/Gross Weight	lbs 18.96/25.13
	kg 8.6/11.4

OUTDOOR SPECIFICATION	
Compressor Type	ROTARY
Compressor Model	KSN98D64UFZ3
Refrigerant	R454B
Refrigerant Oil Charge(mL)	300
Refrigerant Oil	VG74
Outdoor Air Flow (Max) (CFM)	1235.3
Outdoor Noise Level (dBA)	53.0
Dimension (WxDxH)	inch 30.12 x 11.93 x 21.85
	mm 765.0x303.0x555.0
Package (WxDxH)	inch 34.92 x 13.27 x 24.02
	mm 887x337x610
Net/Gross Weight	lbs 59.08/64.37
	kg 26.8/29.2

EFFICIENCY			
Cooling		Heating	
SEER2	21.3	HSPF2-4	9.2
EER2	10.8	COP	3.34

PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	12000
Min/Max Capacity	2700~13800
Moisture Removal(L/h)	1.4
Standard Operating Range(°F/°C)	5~122(-15~50)
Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB


PERFORMANCE of Heating	
Heating (Btu/hr)	
1. @ 47°F Rated	12000
1. @ 47°F Min/Max Capacity	4200~14100
2. @ 17°F Rated	8300
3. @ 5°F Rated: Capacity / COP	8000/1.80
3. @ 5°F Max: Capacity	8000
Standard Operating Range(°F/°C)	5~75(-15~24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

ELECTRICAL	
Power Supply	208/230V,60Hz,1Ph
System MCA	13.0
Connection Wiring	14#x4
System MOCP	15
Compressor RLA	7.5
Outdoor Fan Motor RLA	0.4
Outdoor Fan Motor W	34
Indoor Fan Motor RLA	0.4
Indoor Fan Motor W	30
System Power Input @ Cooling (W)	1111(220 ~ 1430)
System Power Input @ Heating (W)	1053(235 ~ 1310)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	
	W: Fan motor rated output (W)

PIPING	
Throttle type(Indoor)	N/A
Throttle type(Outdoor)	Capillary
Liquid Size	6.35mm(1/4in)
Gas Size	9.52mm(3/8in)
Max. Piping Length(ft/m)	82.00(25)
Max. Height Difference(ft/m)	49.20(15)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/g)	24.69(0.7)
Additional Charge of Refrigerant((oz/ft)/(g/m)	0.16(15)
Connection Method	Flared


NG products are subject to continuous improvements. NG reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations. Actual unit design may differ from images shown in this submittal sheet.

## Indoor Unit Dimension




Capacity	Body Code	W(inch/mm)	D(mm/inch)	H(mm/inch)
6K~9K	A	28-3/4in /729mm	7-7/8in /200mm	11-1/2in /292mm
9K~12K	B	31-5/8in /802mm	7-7/8in /200mm	11-5/8in /295mm
18K	C	38-1/4in /971mm	9in/228mm	12-5/8in /321mm
18K~24K	D	42-5/8in /1082mm	9-1/4in/234mm	13-1/4in /337mm
30K~36K	F	49-5/8in /1259mm	11-1/8in/283mm	14-1/4in /362mm


## Installation Instruction



**Select Installation Location**




NOTE: Based on the position of the wall hole relative to the mounting plate, choose the side from which the piping will exit the unit. You have four options for the exit direction of the piping.



**Indoor unit dimensions(WxH):**  
31.7in(806mm)x11.65in(296mm)

NOTE:  
When the gas side connective pipe is  $\Phi$  (5/8in)16mm or more, the wall hole should be (3-1/2in)90mm.

## Outdoor Unit Dimension



## Installation Instruction

